

Datasheet grease cartridge



Grease cartridge for low-maintenance fifth wheels

Usable for the HOLLAND fifth wheel SK-S 36.20 and low-maintenance competitive products.

Benefits:

- No manual lubrication of lock mechanism required
- Continuously adjustable 1-12 months
- Less grease consumption due to dosing of the quantity
- Time savings
- Lower Cost
- Environmental protection

Key features:

- Automatic single point long term dispenser for grease and oil
- TÜV approved
- Contents: 125 ml
- Operating system: Hydrogen gas formation cell
- Operating pressure max. 3 bar
- Average period of use approx. 6 months
- Operating temperature: -20° C up to +55° C ambient temperature
- Recommended storage temperature of 20° C ±5° C

Safety information:

If the dispenser is put into operation without removing the seal, or if the grease channels of the installation are blocked, the pressure in the dispenser can rise up to 5 bar. When an overpressure of 5 bar is reached, the dispenser bursts at the designated breakage point between housing and funnel. The pressure behind the piston is released and grease or oil can leak out from the designated breakage.

safholland.com

Datasheet grease cartridge



Instructions:

For higher or lower ambient temperatures or varying lubrication requirements, the grease quantity can be continuously adapted on a daily basis. An initial setting of level 6 is recommended.

- Application: The dispenser can be mounted in all conditions
- Important: do not expose directly to heat
- Use within 2 years filling date

The dispensed grease quantity per day is affected by the following:

- Ambient temperature
- Resistance / back pressure in lines
- Viscosity of grease

The simalube can be adjusted or shut off during the period of dispensing. The setting on the adjusting washer refer to standard conditions. It is recommended to check the function of the dispenser (piston movement, targeting unit) at regular intervals.

The trouble free functioning of the lubricant dispensing system is only guaranteed by using the recommended lubricant, the original simalube accessory program and observing the mounting, operating and maintenance regulations. Failure to observe these instructions excludes the manufacturer from liability for any resulting damages.

safholland.com