

## Launch of the new drum brake SNK300x200S

\*\*\*Update\*\*\*

In order to make the launch of the new drum brake SNK300x200S as customer-friendly as possible and to give you our customers more time to include the brake in your vehicle and systems authorization documentation, we have postponed the launch once more.

- In accordance with this change, the start of delivery of the drum brake will now be **September 2016**.

- The axle version **SKxxx 12030 / TDB0487** with a permissible axle load of 11.6t will continue to be deliverable

The following table gives an overview of all axle versions available **from September 2016** with the **SNK300 brakes**. Our customer advisors will be delighted to assist you with any questions or with selecting the right model for your applications.

Axle load	Axle model	Rigid	Self-steering	Forced steering	Brake	Test report TDB	min. r <sub>dyn</sub> *
9t	Z9 3020	x			SNK300x200	0487	348mm
	ZL9 3020		x				
11t	Z11 3020	x			SNK300x200	0487	
	ZL11 3020		x				
11.6t	SKRZ 12030	x			SNK300x200	0487	
	SKRLZ 12030		x				
	SKZRLZ 12030			x			
12t	<b>SKRZ 12030S</b>	<b>x</b>			<b>SNK300x200S</b>	<b>0882</b>	<b>368mm</b>
	<b>SKRLZ 12030S</b>		<b>x</b>				
	<b>SKZRLZ 12030S</b>			<b>x</b>			

\*Smallest permissible tyre radius

### Please note:

The brake must be added to the existing systems and vehicle authorization documentation. The required information is available in advance from our homologation department: Mr Schreck, Tel: +49 6095 301 382, E-mail: [robert.schreck@safholland.de](mailto:robert.schreck@safholland.de) and soon on our website

The extension of the range is scheduled to be implemented in September 2016. From this point, the 12t axle versions will complement the existing range.