

ORDERING GUIDE - OEM

CBX69 TRIDEM SLIDE SUSPENSIONS

USA
SAF-HOLLAND, Inc.
800.876.3929

CANADA
SAF-HOLLAND, Canada Ltd.
519-537-2366



Ordering Guide Information: **PLEASE DOWNLOAD THIS FORM BEFORE COMPLETING.**

This form is designed to collect all necessary information about the suspension application requirements to help determine the appropriate configuration for the trailer build.

For application and selection information, please reference our [Trailer Air Suspension Selection Guide \(XL-AS11415SG-en-US\)](#).

If you have any questions regarding this document, please feel free to contact SAF-HOLLAND Customer Service at 1.888.396.6501.

- Please complete all of the information requested on this ordering guide by filling in all appropriate fields.
- After submitting, print a copy of this ordering guide for your records, by clicking the "PRINT FORM" button.
- To clear the form, click the "CLEAR FORM" button.

How-To Submit This Ordering Guide:

Submit completed ordering guide by clicking the "SUBMIT TO" button next one of our SAF-HOLLAND ordering specialist.

USA

Debbie
Doremire

CANADA

Jim Visser

1. GENERAL INFORMATION

CUSTOMER INFORMATION - VEHICLE MANUFACTURER

Date:

Company Name:

Street Address:

City:

Telephone:

Fax:

Contact Name:

State/Prov.:

Zip/Postal Code:

E-Mail:

END USER INFORMATION - FLEET

Company Name:

Street Address:

City:

Telephone:

Fax:

Contact Name:

State/Prov.:

Zip/Postal Code:

E-Mail:

2. AXLE CONFIGURATION

Axle Track: 71.5" 77.5" Other

Axle Rating: 23,000 Other

Tire Inflation System:

No

MTIS™ Prep ThermALERT™

MTIS™ Prep

Drilled and Tapped, 1-Hole

AERIS™ Prep

Drilled and Tapped, 3-Hole

2.1 AXLE CONFIGURATION - DRUM BRAKES

Drum Brakes - Complete Only If Required - For Disc Brakes, skip Section 2.1 and go to Section 2.2.

WHEEL END OPTIONS

Spindle: Tapered Parallel

Brake Size: 16.5" x 7" 16.5" x 8.63"

Desired Brake Rating: 20k 23k

Brake Shoe/Lining: SAF® Standard Extended Life Linings
 Other


Fully Dressed: Complete Section

Braked Only: STOP! Go To Section 3

Rim Configuration: Dual Wide Base Single

Wheel Material: Aluminum Steel Steel/Aluminum

ABS Sensor Location: None
 Rear
 2 Axle
(Indicate 2 Locations On Image Above)
 All



Hubcap Type: Standard Bolt-On Other

Lube Type: SAE 80/90 Oil Semi-fluid Grease (NLGI 00)
 75/90 Synthetic Oil Other

Tire Brand / Size:

Dust Shields: Yes No

Fasteners Per Wheel End: 2 Ship Nuts 10 Wheel Nuts
 None

Hub Material: Ductile Iron ADI Aluminum None

Auto Brake Adjuster: Standard 5.5"
 Other
 None

Spindle Nut: Standard 3-Piece Nut Pro-Torq® None

Drum Material: Cast Fused None

Bearing: Standard

S-Cam: 28 Spline Standard

Cam Enclosures: Yes No

Brake Chamber: Standard 30/30, 2.5" Stroke
 Other
 None

Hub Style: Hub Piloted

Seal: Standard Spindle Mount Other

2.2 AXLE CONFIGURATION - DISC BRAKES

SAF Disc Brakes - Complete Only If Required - For Drum Brakes, go to Section 2.1

WHEEL END OPTIONS

Model: P89 (5 yr Warranty¹) P89 Plus (7 yr Warranty¹)

Spindle: Parallel Tapered

Brake Rating: 20k 23k 25k


Rim Size: 22.5" 24.5"

Rim Configuration: Dual Wide Base Single

Rim Brand / Type²:

Wheel Material: Aluminum Steel Steel/Aluminum

ABS Sensor Location: None
 Rear
 2 Axle
(Indicate 2 Locations on Image Above)
 All



ABS System³: 2S/1M 4S/2M

Lube Type⁴ (P89 only): SAE 80/90 Oil
 Semi-Fluid Grease (NLGI 00)
 Hard Pack Grease (P89 Plus)

Dust Shields: Yes No

Wheel Nuts: Yes No

ORDERING GUIDE - OEM

CBX69 TRIDEM SLIDE SUSPENSIONS



3. SUSPENSION CONFIGURATION

SLIDER/SUSPENSION INFORMATION						
Axle Arrangement:	Tridem	Ride Height ³ :	16"	16.5"	17"	18"
Slider Model:	CBX69	Box Width:	42"	48"	54"	
Axle Spread:	72" 60"	Body Rail Style:	1.375" x 6" (B-Style) Outside Shim			
Slider Pin Extractor:	QwikRelease™ Air Release		1.375" x 6" (B-Style) Inside Shim			
Shock Straps:	No Yes		1.625" x 4" (H-Style) Outside Shim			
Walk/Drop Solutions:	No PosiLok™	Air Control Kit:	No			
Tank & Mud Flap Bracket Attachments:	No Yes		HCV with Integral Dump 3/8" Low Flow			
Stinger Bracket Attachments:	No Yes		HCV without Integral Dump 3/8"			
			HCV with Integral Dump 3/8" High Flow ⁴			

¹ Standard ABS Sensor is 400 mm Lead Length.

² WARNING: Rim design and/or valve stem configuration may interfere with the air disc brake caliper and cause component damage which could result in the loss of vehicle control causing serious injury or death. Use only rim designs and valve stem configurations that provide proper running clearance (see document XL-SA10070WI). Please check with rim supplier or consult SAF-HOLLAND application engineering team for assistance.

³ Ride height is the nominal unloaded distance from the center line of the axle to the bottom of the slide box. It is recommended that a minimum of 4-1/2" of vertical clearance be maintained above the tires with the trailer in an unloaded condition.

⁴ Not available with PosiLok™

How-To Submit This Ordering Guide:

Submit completed ordering guide by clicking the "SUBMIT TO" button next one of our SAF-HOLLAND ordering specialist.

USA

Debbie
Doremire

CANADA

Jim Visser