

## SAF® Trailer Suspension Axle Systems Equipped with Disc Brakes

### Approved Wheel Part Numbers for use with SAF CBX and ULX Trailer Suspension Axle Systems Equipped with SAF Disc Brakes

#### Please Note:

When specifying wheels to be used with SAF CBX and ULX trailer suspension axle systems equipped with SAF Disc Brakes, please pay special attention to the approved list of wheel profiles listed on the provided table. Specification or installation of non-approved wheel profiles may lead to wheel and caliper interference.

#### Important:

- Dual steel wheels are not approved for SAF Disc Brake suspension systems produced prior to June 2012 with Version 1 head units. See XL-SA10071WI-en-US for identification of Version 1 head units.
- 2" offsets are NOT allowed in combination with the C88 bearing package.

### Approved Wheel Profile Numbers for use with Knorr SK7 & SAF SBS 2220 K0 Calipers configured with C88 & P89 Bearing Packages

Wheel Manufacturer	Wheel Profile No.	C88	P89	Approved Valve Stem	Wheel Material	Wheel Size	Wheel Offset (+) Outset (-) Inset	Wheel Configuration			
Accuride	41644	■	■	TR545D	Aluminum	22.5" x 8.25"		Dual			
	50487	■	■	TR572-E22	Steel						
	50408	■	■								
	28409	■	■	TR573	Steel	24.5" x 8.25"		Dual			
	28641	■	■								
	28827	■	■								
	41362	■	■	TR545D	Aluminum	22.5" x 14"		Wide Base Single			
	50172	■	■	TR543E	Steel						
	29627	N/A	■	TR573							
	41016	■	■	TR543E	Aluminum						
	41140	■	■								
41660	N/A	■									
42142	N/A	■									
Arconic	88367x	■	■	TR554D	Aluminum				22.5" x 8.25"		Dual
	88567x	■	■								
	98367x	■	■	TR555D	Aluminum				24.5" x 8.25"		Wide Base Single
	82262x	■	■	TR553E		22.5" x 12.25"					
	84062x	N/A	■			22.5" x 14"	+0.056				
	84060x	■	■				+2.00				
	84060x	N/A	■	TR555E		0.00					
				+1.00							
Maxion	90262	■	■	TR572-E22	Steel	22.5" x 8.25"		Dual			
	90541	■	■								
	90542	■	■	TR573	Steel	24.5" x 8.25"		Dual			
	90263	■	■								
	90261	■	■								
	10031	■	■	TR575	22.5" x 14"	0.00	Wide Base Single				
10084	N/A	■	TR500	+2.00							
KIC	WH22501	■	■	TR572-E27	Steel	22.5" x 8.25"		Dual			
TCC	2269E	■	■	TR572-F19	Steel	22.5" x 8.25"		Dual			
	2271E	■	■								

**Note:** For specification of wheels not listed in the table, please contact SAF-HOLLAND trailer suspension application engineering.